



FEATURES

- Contains all the quality equipment needed for cutting, welding and brazing in a rugged surrounding plastic carrying case.
- The outfit is designed to carry one 2L acetylene cylinder and one 4L oxygen cylinder.
- As supplied, the outfit can cut to 3/4" (19.1mm) and weld to 1/8" (3.2mm) with larger tips.
- According to different requirements, optional tip sizes are available.



1C016-0001 UW-1515

Including

- | | | |
|--------------------|-----------------------|------------------------|
| 01 Carry Tote | 02 Cutting Attachment | 03 Torch Handle |
| 04 Cutting Nozzle | 05 Oxygen Regulator | 06 Acetylene Regulator |
| 07 Oxygen Cylinder | 08 Acetylene Cylinder | 09 Twin Welding Hose |



Applicable Gas	oxygen and acetylene
Application	medium-volume soldering
Capacity	Cutting up to 3/4" (19.1mm) plate Welding up to 1/8" (3.2mm) plate
Light duty regulator	forged full brass body with durability
Torch handle	stainless steel needle valves with accuracy
Oxygen Inlet	CGA540
Oxygen Outlet	9/16"-18
Acetylene Inlet	CGA200 "MC" tank
Acetylene Outlet	9/16"-18
Oxygen Cylinder	4L (20 CU.FT.) CGA540
Acetylene Cylinder	2L (10 CU.FT.) CGA200
Welding Tips	80V #1, #2
Cutting Tip	1-3-101

Accessories included



3S001-0021	1C003-0006	4P003-0003	4P003-0026	4P003-0009
Goggles	5# green			
Twin Hose	15' x 3/16" (4.5m x 4.8mm) with flame retardancy			
Tote	red injection molded polypropylene carry case			
Lighter	single flint			
Tip Cleaner	80mm / 100mm			
Wrench	multi functional			

NOTE: All regulators, torch handle, cutting attachment, welding tips can be changed according to your required models. **Check Valve & Propane Cylinder Available**

1Mpa = 1000Kpa = 10.197 Kgf/cm² = 145.04psi, 1 m³/h = 16.67 LPM = 35.32 SCFH