Wanna have your **OWN EXCLUSIVE** welding & cutting kit? Come to UWELD!

YOU MAKE A LIST, WE DELIVER A KIT AND MORE ...





10016-0101

NM-250 Model is principally intended for general workshop cutting up to 300mm (12") capacity.

The balance and trim combined with 480mm (18") length make it ideally suited for most industrial applications.

- . Designed for oxy/fuel gas cutting of steel up to 300mm(12") thickness using oxygen with either acetylene or propane as
- . For use with ANME (acetylene) or PNME (propane) cutting nozzles.
- . 3/8"BSP hose connection
- . Gas type: Acetylene or propane
- · Length: 480mm
- · Head angle: 90 degrees

Acetylene Inlet G5/8"-LH Acetylene Outlet G3/8" Oxygen Inlet G5/8"-RH Oxygen Outlet G3/8"



1C016-0103

Capacity: cutting up to 100mm (4"). Welding up from 0.5mm to 6.0mm

Unique cutting oxygen flow valve creates a progressive piercing and the smoothest cutting conditions.

Die forged brass head for added strength and durability. Hose connection M16*1.5

Oxygen Inlet G3/4 Oxygen Outlet M16*1.5 Propane Inlet G7/8

015 | Catalogue 2016-2018







1C016-0104

It is a tried and tested blowpipe designed for lightweight production welding and maintenance.

It is a complete welding and cutting blowpipe of proven design.

- · Exceptionally comfortable in use.
- · High integrity trim valves.
- · Light and positive, ideal for high quality welding.
- Precision engineered mixer for precise gas control.
 All positional facility for nozzles through the serrated
- · Parallel tubes for increased visibility when in use.
- . High tensile brass head for extended service life.
- · Piston cutting oxygen valve provides smooth cutting action.

Cuts up to 50mm plate Welds up to 8mm plate



1C016-0105

It is a tried and tested blowpipe designed for lightweight production

It is a complete welding and cutting blowpipe of proven design.

Feature:

- · Exceptionally comfortable in use.
- · High integrity trim valves.
- · Light and positive, ideal for high quality welding.
- Precision engineered mixer for precise gas control.
 All positional facility for nozzles through the serrated
- · Parallel tubes for increased visibility when in use.
- · High tensile brass head for extended service life.
- · Piston cutting oxygen valve provides smooth cutting action.

Cuts up to 50mm plate

Welds up to 8mm plate

019 | Catalogue 2016-2018