



Standard burner

1C022-0053

Standard burners with brush-type flames for all kinds of soft soldering/small heating applications
Silver soldering about 615°C
For connection to Sievert Pro necktubes
Recommended work pressure 2 bar



Burner diameter	Gas consumption, at 4 bar	Effect
22mm	240g/h	3,1kw
Soft soldering about 400°C max. pipe diameter		40mm



Power burner

1C022-0054

Heavy duty light weight power burners with extremely strong and windproof flames to withstand the severest weather conditions

Ideal for drying, bitumen laying, detail and field torching, preheating before welding, melting snow/ice and other heat deman and field torching, preheating before welding, melting snow/ice and other heat demanding applications

For connection to Sievert Pro necktubes
Recommended work pressure 4 bar



Burner diameter	Gas consumption	Effect
32mm	2000g/h	26kW
Made of high quality brass		



Power burner

1C022-0055

Heavy duty light weight power burners with extremely strong and windproof flames to withstand the severest weather conditions

Ideal for drying, bitumen laying, detail and field torching, preheating before welding, melting snow/ice and other heat deman and field torching, preheating before welding, melting snow/ice and other heat demanding applications

For connection to Sievert Pro necktubes
Recommended work pressure 4 bar



Burner diameter	Gas consumption	Effect
35mm	3350g/h	43.5kW
Made of high quality brass		



Power burner

1C022-0056

Heavy duty light weight power burners with extremely strong and windproof flames to withstand the severest weather conditions

Ideal for drying, bitumen laying, detail and field torching, preheating before welding, melting snow/ice and other heat deman and field torching, preheating before welding, melting snow/ice and other heat demanding applications

For connection to Sievert Pro necktubes
Recommended work pressure 4 bar



Burner diameter	Gas consumption	Effect
50mm	6700g/h	86kW
Made of high quality brass		